



DUCKHAMS BRAKE FLUID DOT4

DUCKHAMS BRAKE FLUID DOT4 provided the level of brake and clutch for heavy duty disc and drum brake designed for used in both brake and clutch. Performance is higher with premium Boiling Point, Brake Fluid DOT4 does not cause corrosion and also has high-quality international standard SAE J1704, FMVSS No 116 DOT 4.

Meet Performance :

- SAE J1704
- FMVSS No 116 DOT4
- ISO 4925 Class 4

Applications :

- Suitable for hydraulic brake system, hydraulic clutch systems.
- Suitable for car, pick up, bus & truck, and motorcycle.
- Stop and go condition with potentially generating high temperature in brake system

Features and Benefits :

- Resistant to high temperatures, High Boiling Point to help prevent vapour lock
- Corrosion Protection
- Not reacting to rubber and components in the brake system rubber seal not shrink or expand, too.
- less absorption of water, provides higher boiling point.

Typical Properties :

Properties	Test Method	Typical value
Specific Density @20/20 deg C	DM40	1.033
ERBP (Equilibrium Reflex Boiling Point)	SAE J1704	240
WERBP (Wet Equilibrium Reflex Boiling Point)	SAE J1704	163
Water content	Karl Fisher	0.1
pH value	SAE J1704	9.5
Viscosity at -40°C	SAE J1704	1315
Viscosity at 100°C	SAE J1704	2.16

These descriptions are typical of current production. Whilst future production will conform to Duckhams' specification, variations in there description may occurs.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use.

Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Duckhams or others is not to be inferred from any statement contained herein.