



# DUCKHAMS EURO 6 SUPREME 5W-30

DUCKHAMS EURO 6 SUPREME 5W-30 is a superior semi-synthetic, high-performance engine oil designed for modern diesel and gasoline engines equipped with aftertreatment systems. It delivers fuel economy, superior engine protection, and features mid-SAPS formulation for optimal compatibility. Suitable for extended oil drain intervals, it provides stable, stay-in-grade performance across a wide range of high-performance vehicles.

## Meets Performance:

- ACEA C3-21, C2-21
- API SP

## Applications :

- Ideal for modern EuroV&VI diesel engines equipped with exhaust gas after-treatment systems ie DPF & SCR.
- Also suitable for diesel Euro III & II engine
- Works well with gasoline both modern GDI and previous PFI engine

## Features and Benefits :

- Developed with Mid SAPS technology not only enhancing engine protection but also unharmlful to all after treatment devices
- Protect aftertreatment devices ie GPF/DPF/SCR/OCD
- Better protection and engine cleaner for previous Euro II & III diesel and gasoline engines

## Typical Properties :

| Description                     | Unit    | Test instrument  | Typical value  |
|---------------------------------|---------|------------------|----------------|
| Appearance                      | -       | Visual           | Bright & Clear |
| ASTM Color                      | -       | ASTM D1500/D6045 | L3.0           |
| Density @15 °C                  | g/cm³   | ASTM D4052       | 0.8514         |
| Kinematic Viscosity @40 °C      | mm²/s   | ASTM D445        | 69.50          |
| Kinematic Viscosity @100 °C     | mm²/s   | ASTM D445        | 11.78          |
| Viscosity Index                 | -       | ASTM D2270       | 162            |
| Flash Point, COC                | deg C   | ASTM D92         | 228            |
| Pour Point                      | deg C   | ASTM D5950/D6892 | -45            |
| Total Base Number               | mgKOH/g | ASTM D2896       | 6.40           |
| Cold Cranking Simulator@ -30 °C | mPa.s   | ASTM D5293       | 6,706          |

## Pack : (3X6L+1L)

These descriptions are typical of current production. Whilst future production will conform to Duckhams' specification, variations in there description may occurs.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use.

Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Duckhams or others is not to be inferred from any statement contained herein.