



DUCKHAMS GREASE GP3

DUCKHAMS GREASE GP is general purpose calcium grease formulated with mineral oil, calcium soap and contains additive to improve adhesive and water resistance properties.

Applications :

This grease is recommended for general purpose application at normal temperature and wet condition.

- Uses in automotive and industrial applications.
- Uses in chassis and suspension system for motor vehicles of farm tractors such as ball joints, shift joints and coil springs.
- Water pumps bearing
- The recommended operating temperature is normal operating temperature up to 70oC

Features and Benefits :

- Excellent adhesion and water resistance
- Protect metal surface from rust and corrosion
- Prevent dust and dirt in the moving parts

DUCKHAMS
KEEPS YOUR MACHINERY

Typical Properties :

Properties	Test Method	Typical value
Soap Type	-	Calcium
Texture	Visual	Fibrous
Color	Visual	RED
Kinematic Viscosity @40°C	ASTM D445	340
Kinematic Viscosity @100°C, cSt.	ASTM D445	14.40
Unworked Penetration @ 25oC, mm/10	ASTM D217	228
Worked Penetration @ 25oC, mm/10	ASTM D217	227
Dropping Point, oC	ASTM D566	107
Foaming: Seq. II @93.5°C, Tendency/Stability	ASTM D566	0/0

These descriptions are typical of current production. Whilst future production will conform to Duckhams' specification, variations in there description may occurs.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use.

Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Duckhams or others is not to be inferred from any statement contained herein.